

2" Fireplug Vent Model # FP2011



Eave Vents	Model	Size W x L	NFVA Provided	Flanges Available	Flange Definition	Weight
	FP2011	1-7/8" diameter	1.2 sq in	1/2" Flange Front	Flange Front	0.2 lbs
Continuous Soffit and Custom sizes/materials AVAILABLE						

BENEFITS:

- Safety vents that are used in areas prone to wildfires, wind driven rain, or wind driven snow.
- Overlapping Baffle Protection (Patented) plus 1/16" mesh plate on the back side
 - Air Flows through normally
 - Compliant with ASTM E2886/2912 Tests for flames, embers and radiant heat
- Approved for use throughout California and beyond (Calfire BML Approval # 8165-2232:0501)
- Anti-Clogging
- Prevents Rodent Entry
- 20 Year Warranty
- Easy to Install, Retrofit and Paint (comes with pre-drilled holes)

STANDARD MATERIALS

ASTM A653/A653M- G90 hot dipped galvanized steel, 26GA
 ASTM D9092- mill phosphatized coating for painting. IF BONDERIZED
 ASTM b370- Sheet Copper, 16oz and 20oz IF GALVANIZED
 .025 x.025 hot dipped galvanized 23ga wire mesh

Installation:

Install with "T" on the top. See website: www.brandguardvents.com for installation instructions and video.
 Product is intended to be used only under a roof overhang inserted into 2x blocking/frieze block. It is not intended to be used on a sidewall without a protective roof overhang.